

Category 7 S/FTP EuroClass C_{CA} Cables

Datasheet: GD103155v6


Brand-Rex | a **LEVITON** company

APPLICATION

Brand-Rex UM10 cables exceed the Category 7 performance standards. They are specified to 600MHz and rated to 1000MHz and are suitable for use in all Class F structured wiring cable systems. The applications supported include 10 Gigabit Ethernet, Gigabit Ethernet, Power over Ethernet and broadband video transmissions at frequencies up to 600MHz.

FEATURES AND BENEFITS

- 23 AWG solid annealed copper wire
- 4 twisted pairs individually screened and cabled together – providing EMI immunity
- Overall braided screen – for improved shielding efficiency, increased mechanical robustness and heat dissipation
- Designed to Support all Class F protocols including 10GBASE-T
- Supports Power over Ethernet (PoE) and Power over Ethernet Plus (PoE+) Applications
- Enhanced HFFR-LS* material enables the cable to meet the requirements of the Construction Products Regulation (CPR) EuroClass C_{CA}
- Green† coloured jacket to identify EuroClass level C_{CA}
- Included in the Leviton and Brand-Rex 25 Year System Warranties when used in conjunction with Leviton or Brand-Rex copper connectivity. System warranties available for qualified projects installed by certified contractors.



* Halogen Free Flame Retardant – Low Smoke
† Also available in a range of non-standard colours

STANDARDS

Applicable Cable Standards: IEC 61156-5 and EN50288-4-1

REACTION TO FIRE

CHARACTERISTIC	STANDARD	RATING	DUPLEX RATING
Single Cable Flame Rating	IEC/EN 60332-1-2	Pass	Pass
Smoke Production	EN 61034	Pass	Pass
Acid Gas Emission / Acidity	EN 50267-2-3	Pass	Pass
Classification	EN 13501-6	C _{CA} s1a d0 a1	C _{CA} s1a d1 a1

Category 7 S/FTP EuroClass C_{CA} Cables

Datasheet: GD103155v6



PRIMARY ELECTRICAL PARAMETERS

CHARACTERISTIC	SPECIFICATION	TYPICAL PERFORMANCE @ 20°C
Conductor Loop Resistance	Max 19 Ω / 100m	14Ω / 100m
Conductor Resistance Unbalance	Max 2%	0.1%
Insulation Resistance	>5GΩ.km	>50GΩ.km
Dielectric Strength	2500 Vdc/2secs	Pass

SECONDARY ELECTRICAL PARAMETERS

CHARACTERISTIC	SPECIFICATION	TYPICAL PERFORMANCE @ 20°C
Velocity of Propagation	<534nsec/100m @ 100MHz	413nsec/100m @ 100MHz
Delay Skew	Max 25nsec/100m @ 100MHz	4nsec/100m @ 100MHz
Mean Characteristic Impedance	100Ω +/- 5Ω @ 100MHz	100Ω ± 3Ω @ 100MHz
Coupling Attenuation	Type 1	90dB
Transfer Impedance	Grade 1	8mΩ/m @ 10MHz

ELECTRICAL PERFORMANCE

Frequency (MHz)		1	4	10	100	200	250	500	600	1000
Insertion Loss (dB/100m)	Standard	2.0	3.6	5.7	18.5	26.8	30.2	44.1	48.9	na
	<i>Typical</i>	1.9	3.5	5.5	18.0	26.1	29.4	43.0	47.6	63.8
NEXT (dB)	Standard	80.0	80.0	80.0	72.4	67.9	66.5	61.9	60.8	na
	<i>Typical</i>	100.0	100.0	100.0	94.3	88.9	87.1	81.7	80.3	76.3
PSNEXT (dB)	Standard	77.0	77.0	77.0	69.4	64.9	63.5	58.9	57.8	na
	<i>Typical</i>	97.0	97.0	97.0	91.3	85.9	84.1	78.7	77.3	73.3
ELFEXT (dB/100m)	Standard	80.0	80.0	74.0	54.0	48.0	46.0	40.0	38.4	na
	<i>Typical</i>	90.0	90.0	90.0	70.8	64.8	62.8	56.8	55.2	50.8
PSELFEXT (dB/100m)	Standard	77.0	77.0	71.0	51.0	45.0	43.0	37.0	35.4	na
	<i>Typical</i>	87.0	87.0	87.0	67.8	61.8	59.8	53.8	52.2	47.8
Return Loss (dB)	Standard	Na	23.0	25.0	20.1	18.0	17.3	17.3	18.3	na
	<i>Typical</i>	27.0	30.0	30.0	25.1	23.0	22.3	20.2	19.7	18.1
ACR (dB/100m)	<i>Typical</i>	98.1	96.5	94.5	76.3	62.8	57.7	38.7	32.6	12.5
PSACR (dB/100m)	<i>Typical</i>	95.1	93.5	91.5	73.3	59.8	54.7	35.7	29.6	9.5

Category 7 S/FTP EuroClass C_{CA} Cables

Datasheet: GD103155v6



INSTALLATION

Temperature (Installation)	0°C to +50°C	Min Bend Radius (Installation)	8 x Outer Diameter
Temperature (Operation)	-20°C to +75°C	Min Bend Radius (Operation)	4 x Outer Diameter
Max Tensile Load (Installation)	10kg per simplex cable	Field Test NVP Value	0.80
Segregation Class	Class D		

PRINT LEGEND

Example print legend:

[Length Mark]m BRAND-REX a LEVITON company UM10-Cca Cat 7 S/FTP EN 50399 EuroClass Cca s1a d0 a1 NVP 0.80
MADE IN UK [ID number] [Week/Year]

REEL PACKAGING SPECIFICATIONS

Brand-Rex Part Number	Packaging Length (m)	Colour	Nominal Cable Dimensions (mm)	Nominal Cable Weight (kg/km)	Reel Size Flange x Width (mm)	Gross Weight (kg/Item)	Items Per Pallet
UM10-Cca-500GN	500	Green†	7.2	52.7	400 x 390	28.9	12
UM10-Cca-1000GN	1000	Green†	7.2	52.7	600 x 405	59.2	4
UM10-Cca-D500GN††	500	Green†	7.1 x 14.4	102.2	600 x 405	57.6	4

† Also available in a range of non-standard colours

†† Duplex Cable

*“Brand-Rex is **dedicated** to **designing, developing** and **manufacturing** sustainable **high performance** structured cabling and speciality **cabling solutions**”*

The information contained in this document is valid and correct at the time of issue. Brand-Rex reserves the right to modify details without notice in light of subsequent standard/specification changes and ongoing technical developments.

DECLARATION OF PERFORMANCE**DoP No. 00049**

Annex III Construction Product Regulation (EU) No 305/2011.

For the Construction product: Communication cables

1. Unique identification code of the product-type

UM10 Cca / Cat 7 S/FTP Cca

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

As per Product Label

3. Intended use or uses of the construction product

Supply of communications in buildings and other civil engineering works with the objective of limiting the generation and spread of fire and smoke.

4. Contact address of the manufacturer
According to Article 11(5):Brand-Rex Ltd, Viewfield Industrial Estate, Glenrothes
Fife, KY6 2RS, Scotland, UK
Tel: +441592772124 Fax: +441592775314
Email: support@brand-rex.com5. Contact address of authorized representative:
According to Article 12(2):

As per Item 4.

6. System of assessment and verification of constancy of performance of the construction product as set out in CPR EU No.305/2011 Annex V.

System 1+

7. Notified product certification body

Performed the determination of product type, the initial inspection of the manufacturing plant and of FPC, the continuous surveillance, assessment and evaluation of the FPC and the audit testing of samples taken before placing the product on the market and issued the constancy of performance.

NB2661

8. Declared performance

Essential characteristics	Performance	Harmonized technical standard
Reaction to fire	Cca-s1a,d0,a1	En 50575: 2014
Release of dangerous substances	None	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ken Hodge, Senior Director, Engineering

(Name and function)

Glenrothes, 11th May 2017

(Place and date of issue)


(Signed or on behalf of)